



Hydro-lution

The evolution of G-Drink never ends. The most successful Glass Front Vendor of our history presented in a new look. A spacious and brightly illuminated showcase enhances the product visibility. An innovative capacitive key pad with back lit numerals provide high visibility in light and dark places. New user friendly features offer a large display in blue characters with a new easy door latching system.

DC6 / DT6

G-Drink Design DC6 (Std) / DT6 (Touch) Vertical

TECHNICAL SPECIFICATIONS

DC6 / DT6

DIMENSIONS H x W x D (mm)	1830* x 940 x 845
WEIGHT (NET - Standard machine without options)	295 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 30 / Max. 42
MAX. CAPACITY (0.33 l CANS)	336
MAX. CAPACITY (0.50 l PET BOTTLES)	240
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
MAX. POWER CONSUMPTION	800 W
POWER SUPPLY	230 V / 50 Hz
ENERGY CLASS	F - F (HC-R290)
ENERGY CONSUMPTION - kWh/annum	1843 - 1988 (HC-R290)

OPTIONAL

- CUSTOMIZED CABINET COLOUR
- SPECIAL CODED LOCK (RIELDA)
- ANTI-VANDALISM KEY PAD AND SAFETY COIN INSERT
- WALL/FLOOR FIXING KIT
- LOCK PROTECTION
- FRONT GLASS PROTECTION
- PRODUCT SPACERS
- VARIOUS FITTING KITS
- BRANDING
- SECURITY CASH BOX SYSTEM
- CO2 COOLING UNIT AVAILABLE

* With adjustable leveling screw

The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment